

Circular Saw CXT HS301DWAE



Product Description

12V MAX • 1 500 min⁻¹ • 85 mm

Small circular saw for light use

A small and light hand-held circular saw for small jobs. A speed of 1 500 min⁻¹, and blade diameter of 85 mm that offers a maximum cutting depth of 25,5 mm. Dust removal function helps keep cut line visible. Blade diameter of 85 mm, max. cutting depth of 25,5 mm. Two 2.0Ah batteries and a charger in a case

Product Features

- ⊙ Tilting base for bevel cuts from 0° - 45°
- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381805278

Product Specifications

| | |
|---|------------------------|
| Bore Size (Arbor Diameter) | 15 mm |
| Tool weight with battery (EPTA) | 1,6 - 1,7 kg |
| Max. Cutting Depth at 45° | 16,5 mm |
| Capacity 45° (Miter R/L 45°, Bevel 0°) | 16,5 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Rake Angle | 45° |
| Battery Voltage | 12 V |
| Sound Pressure Level | 86 dB(A) |
| Max. Bevel Range (Left) | 0 / 45 ° |
| CXT Battery | 1 |
| Product Dimensions (L x W x H): | 313 x 170 x 155 mm |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| System | CXT 12Vmax |
| Vibration Level (3 axes) | ≤ 2,5 m/s ² |
| Product net weight (new) | 1,4 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vacuum cleaner connection Ø in / out | 25/31 mm |
| Max. Cutting Depth at 90° | 25,5 mm |
| Blade Diameter | 85 mm |
| Tool Category | Sawing |
| No load speed | 1500 min ⁻¹ |

Standard Equipment

- ⦿ 1pc DC10WC standard charger
- ⦿ 2pcs BL1021B (2.0Ah) CXT Battery
- ⦿ Carry Case

More info

<https://makita.ae/product/circular-saw-cxt-hs301dwae/>