

Classifications

EN ISO 14343-A	AWS A5.9 / SFA-5.9
W 19 9 L	ER308L

Characteristics and typical fields of application

TIG rod of W 19 9 L / ER308L type for welding 1.4306 / 304L, 304LN steel grades. Controlled weld metal ferrite content, 3 – 8 FN (stricter on demand), particularly for good cryogenic toughness and lateral expansion down to –196°C. Max. service temperature 350°C.

Base materials

1.4301 X5CrNi18-10, 1.4306 X2CrNi19-11, 1.4307 X2CrNi18-9, 1.4311 X2CrNiN18-9, 1.4312 GX10CrNi18-8, 1.4541 X6CrNiTi18-10, 1.4546 X5CrNiNb18-10, 1.4550 X6CrNiNb18-10
UNS S30400, S30403, S30453, S32100, S34700
AISI 304, 304L, 304LN, 302, 321, 347

Typical analysis


	C	Si	Mn	Cr	Ni	FN
wt.-%	0.02	0.5	1.8	20	10.0	3 – 8

Mechanical properties of all-weld metal - typical values (min. values)

Condition	Yield strength	Tensile strength	Elongation A	Impact energy ISO-V KV J		Lateral expansion
	R _{p0.2}	R _m	(L ₀ =5d ₀)	20°C	–196°C	mm
	MPa	MPa	%			–196°C
u	430 (≥ 320)	550 (≥ 510)	38 (≥ 25)	150 (≥ 100)	65 (≥ 32)	≥ 0.38

u untreated, as-welded – shielding gas Ar

Operating data

	Polarity	DC-	Dimension mm
	Shielding gas (EN ISO 14175)	I1	1.6 × 1000
	Rod marking	W 19 9 L / ER308L	2.0 × 1000
			2.4 × 1000
			3.2 × 1000

Heat input max. 1.5 kJ/mm, interpass temperature max. 100°C.

Approvals

-